
DIGITUS® Modular plugs for flat cable

A-MO 6/6 SF

EAN 4016032065135



Modular Plug, for Flat Cable, 6P6C unshielded, DIP, 6 µ gold

These modular plugs can be used to establish quick and simple connections.

- Layout performance: CAT 3, 1GBase-T
- Area of application: Patch cable assembly
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- UL certified
- Technical properties:
- Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.6 ⊠ gold-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: ⊠ 20N
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -40 °C to +80 °C
- Current carrying capacity: 1A -1.5A at 50 °C

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10000	9.70	41.50	29.00	22.00	26,477.00
Packaging Unit Inside	100	97.00	2.00	15.00	20.00	600.00
Packaging Unit Single	100	97.00	2.00	15.00	20.00	600.00
Net single without Packaging	0	1.00	1.50	1.00	1.00	1.50

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.