DIGITUS® DisplayPort Connection Cable, 1m

AK-340100-010-S

EAN 4016032288916



DisplayPort Connection Cable, Type DP M/M, 1.0m, w/interlock, UHD 4K, DP 1.2, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support up to 4K/2K with 60Hz
- Supported Video Resolution: 4K (3840x2160) @ 60 Hz, Full HD (1920x1080) @ 120 Hz
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)
- HDCP-Version: HDCP 1.3

Attributes


- Assortment: DisplayPort Cables
- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Wire material: CCS
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:


AK-340100-010-S
DisplayPort Connection Cable
DIGITUS


AK-340100-010-S
DisplayPort Connection Cable
DIGITUS

