# DIGITUS® Keystone housing for top-hat rail mounting, IP20

**AN-25186**

**EAN 4016032372981**



**DIN-Rail adapter for 1x Keystone Modules, IP20 labeling field, earthing spring, side cover**

The Keystone module is mounted in the housing on the top-hat rail. The distance between the top-hat rail and the wall should be around 10 mm. Up to 12 modules can be installed in series in the distribution box. The IP20 degree of protection is only guaranteed if the housing is installed with covers. The delivery does not include the Keystone module.

**Quick installation and high functionality for every control cabinet**

- Keystone mount version: 45° angled outlet
- Areas of application: Electrical distribution boxes
- Standards: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C

- General properties:
- Suitable for installation on the top-hat rail in electrical distribution boxes
- Integrated dust protection flap
- Side cover caps included in the scope of delivery
- Protection class IP20
- Technical features:
- Housing material: ABS UL-94V-0
- Physical properties:
- Operating temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

**Logistics**

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|---|---|---|---|---|---|---|
| **Packaging Unit Carton** | 1 | 0.20 | 7.00 | 7.00 | 2.00 | 98.00 |
| **Packaging Unit Inside** | 1 | 0.20 | 7.00 | 7.00 | 2.00 | 98.00 |
| **Packaging Unit Single** | 1 | 0.20 | 7.00 | 7.00 | 2.00 | 98.00 |
| **Net single without Packaging** | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |


Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

**More images:**






