DIGITUS® USB-C 4.Gen3 - USB-C connection cable, 1m

DB-300443-010-S

EAN 4016032485865



USB4 Gen3 connection cable,TypeC to TypeC,Alu-Hous PP braid 8K@60Hz,4K@60Hz,PD3.1, 40Gbits/s, 1m, bl.

The Digitus® 3rd generation USB 4.0 cable with aluminum housing is the all-rounder among cables. Thanks to the Thunderbolt 3 protocol, PCI Express, DisplayPort and host-to-host transmissions can be realized. You can use this cable to transfer audio/video signals, data and power. The data transfer speed is 40 Gbit/s, which is 8x faster than USB 3.0 (5 Gbit/s), 4x faster than USB 3.1 (10 Gbit/s) and 2x faster than USB 3.2 (20 Gbit/s). This allows you to transfer large data such as movies and music within seconds. The video signals are transmitted in max. 8K at a refresh rate of 60 Hz. In addition, the resolution 4K (3840 x 2160) @60Hz. (dual mode possible) is also supported. Thanks to USB Power Delivery Revision 3.1, the fast charging function is guaranteed. With the corresponding charger, you can charge your smart devices with max. 240 W (5 A / 48 V) in a short time. The USB Type-C interface enables broad compatibility with devices with this connection.

The USB4 Gen3 cable is an all-rounder and supports the following transmission types: audio/video/data transfer/charging function

- Supports: 8K (7680x4320) @60Hz.
- Supports: 4K (3840 x 2160) @60Hz. (Dual possible)
- Supports data transfer rates of up to 40 Gbit/s
- Backwards compatible with Thunderbolt 3, USB 3.2, USB 3.1 and USB 2.0
- Supports USB Power Delivery Revision 3.1 (PD 3.1) with 48V, 5A and 240W
- Core material: CU
- Connection 1: USB type C, plug
- Connection 2: USB type C, plug
- Dimension plug 1 : 6.65*2.4mm
- Dimension plug 2 : 6.65*2.4mm
- Color connections: Black
- Contact surface: gold-plated
- Number of PINS: 22
- Hood: potted
- Cable outer material: PP
- Plug housing: Aluminum
- Cable outer diameter: 5.0 mm
- Tensile strength: 4 kg/min
- AWG: 30
- 5A 48V
- Bending radius: 60
- Cable color: Black
- Shielding: Double shielded
- USB-C product: yes
- Total weight: 45g
- Manufacturer's instructions:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, please make sure that your USB-C display supports DisplayPort signal output.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.
- To use a dual 4K output, the USB 4 device must support the PD3.1 protocol

Attributes

- AWG: 32
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: gold-plated
- Ferrite filter: none
- USB compliance: USB 4.0
- Length: 1 m
- Shielding: Double shielding

Package contents

- 1x USB 4.0 Type-C connection cable

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	6,185.00	26.00	50.00	23.00	29,900.00
Packaging Unit Inside	20	1.55	12.00	24.00	21.00	6,048.00
Packaging Unit Single	1	0.08	5.50	23.00	2.00	253.00
Net single without Packaging	0	54.00	100.00	16.00	1.00	1,600.00

More images:










