DIGITUS® colored pigtails, SC OM3 50/125 µ, Simplex

DK-25221-02/3

EAN 4016032262992



FO pigtail set, 12 pcs., SC, MM OM3 50/125 µ loose buffer, color code DIN IEC 304, 2 m

The DIGITUS® Fiber Optic Colored Pigtails are available as LC Simplex, SC Simplex and ST Simplex version and offer with the classes OS2, OM2, OM3 and OM4 best performance and link quality for your network. The connector conforms acc. IEC 61754-4 2002 and is equipped with a Zirconia ceramic ferrule. The colored buffers are color coded according to IEC 304 (white, violet, turquoise, black, red, pink, orange, gray, green, yellow, brown, blue).

Future-oriented standards and high-end quality for your network.

- Simplex OM 3 50/125µ 2 m
- Colored buffer, according to IEC 304 in the colors white, violet, turquoise, black, red, pink, orange, grey, green, yellow, brown, blue
- 12 pcs in package
- Loose buffer
- Return loss MM PC: > 25 dB
- Zirconia ceramic ferrule
- Simplex OM2 50/125 µ 2 m
- Secondary coating dimensions: Ø 0.9 ± 0.1 mm
- Primary coating: Acrylate; Ø 250 ± 15 µm
- Colored buffer, according to IEC 304 in the colors white, violet, turquoise, black, red, pink, orange, grey, green, yellow, brown, blue
- 12 pcs in package
- Loose buffer

Attributes

- Boot: single-color
- Cable jacket: LSOH
- Connector 1: SC
- Connector 2: SC
- Fiber class: OM3
- Fiber diameter: 50/125µ
- Mode: Multimode
- Length: 2 m

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	160	14.07	60.00	38.00	32.00	72,960.00
Packaging Unit Inside	20	1.76	18.00	19.50	14.00	4,914.00
Packaging Unit Single	1	0.09	2.00	20.00	30.00	1,200.00
Net single without Packaging	0	0.07	17.00	18.00	2.00	612.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.