DIGITUS® Installation Cable Indoor/Outdoor A/I-DQ (ZN) BH 9/125µ OS2, 24 fibers, CPR Dca, LSZH

DK-39242-U

EAN 4016032452270



FO A-I-DQ(ZN)BH 24E9/125µ, SM, OS2, 24 fibers Indoor/Outdoor, LSZH, Dca, black, length 1 m

Multi tube cable is a design that has high tensile strength and flexibility in a compact cable size. Our loose tube cable provides excellent optical transmission and physical performance. We ensure a continuing level of quality in our cable products through several quality control programs including ISO 9001 and all the materials have passed REACH and ROHS. We ensure product reliability through rigorous qualification testing of each product family. Both initial and periodic qualification testing are performed to assure the cable's performance and durability in the field environments

- LSZH – low smoke zero halogen
- UV-resistant
- Longitudinaly and laterally water-resistant
- Glass yarn armoured
- Non-metal rodent protection
- Metal free
- Attenuation at 1310nm : ⊠ max. 0.34 dB/km (before cabling) ; ⊠ max. 0.36 dB/km (after cabling)
- Attenuation at 1550nm: ⊠ max. 0.21 dB/km (before cabling) ; ⊠ max. 0.22 dB/km (after cabling)
- Attenuation at 1625nm : ⊠ max. 0.23 dB/km (before cabling) ; ⊠ max. 0.25 dB/km (after cabling)
- Zero Dispersion Wavelength : 1302 ~ 1324 nm
- Zero Dispersion Slope : ⊠ 0.092 ps/nm 2 x km
- PMD Link value (M= 20 cables Q= 0.01%) max. PMDQ : 0.2 ps/⊠km
- Cable Cutoff Wavelength (⊠cc) : ⊠ 1260 nm
- Macro bending Loss (100 turns ; ⊠50nm) at 1550 nm : ⊠ 0.05 dB
- Macro bending Loss (100 turns ; ⊠50nm) at 1625 nm : ⊠ 0.10 dB
- Mode Field Diameter at 1310nm : 9.2 ± 0.4 µm
- Cladding diameter : 125 ± 1 µm
- Core/ clad concentricity error : ⊠ 0.6 µm
- Cladding Non-Circularity : ⊠ 1.0 %
- Proof stress : ⊠ 0.69 Gpa
- Fiber count (OS2 G.652) : 2 ~ 72 pc
- Max. number of loose tube : 6 pc
- Fiber number per tube : 12 pc
- Loose tube : 2.3 ± 0.2 mm
- Strenght member : FRP
- Outer sheath : material : LSZH, CPR Dca, EN 50575: 2014+ A1: 2016 ; thickness : 1,6mm ; diameter : 12.0 ± 0.5mm
- Max. allowable pulling force : 1500 N
- Crush resistance : 1000/300 N/100mm
- Cable weight : 300 ± 10 % kg/km
- Standard lenght : 4 ± 5 % KMS
- Temperature range : transport and storage : - 40°C to + 70°C ; installation : - 40°C to + 60°C ; operation : - 40°C to + 70°C

Attributes


- Application: universal
- Cable jacket: LSOH
- Cable type: U-DQ (ZN) BH X E 9/125µm
- Color cable: black
- Fiber class: OS2
- Fiber diameter: 9/125µ
- Mode: Singlemode
- Number of fibers: 24

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:


LSOH Outer Sheath
E-glass yarn
Water blocking tape
Filler elements
Loose tube
Strength Member FRP
Water blocking yarn
Fibers
Jelly
Ripcord