DIGITUS® All-in-one UPS, 600VA/360W, LED

DN-170110

EAN 4016032456575



All-in-One UPS, 600VA/360W, LED 12V/7Ah x1, 4x CEE 7/7,3x IEC C13, USB, RJ45

The Line-Interactive UPS models offer protection against power failure, overvoltage damage, data loss and much more. User-friendly handling, a high level of performance and safety thanks to the integrated microprocessor control unit characterize the Line-Interactive series. Protect yourself against data loss and damage to your devices in the home and office. Protect your devices with the AVR function, which automatically provides the correct voltage and prevents overvoltage and undervoltage. Further safety features such as overload / discharge and overcharge protection as well as cold start and energy saving functions round off this UPS series. Data loss and damage are a thing of the past with this UPS system.

All-in-one: Reliable protection against data and power failure, surge damage for your connected devices

- 4 x socket outlets with earthing contact for connecting your appliances
- 3 x IEC C13 socket for connecting monitors, for example
- 1 x USB type A socket for charging mobile devices with 5 V / 2 A max.
- 1 x USB type-B socket for software communication
- 1 x RJ45 input / output as surge protection for your Internet access + software communication
- LED display for the following functions: Supply via mains voltage / Supply via battery voltage / Error message
- Audible error message for the following events: Power failure (10 sec.) / Low battery (1 sec.) / Overload (0.5 sec.) / Error (continuous tone)
- Protective functions: Discharge / overcharge / overload
- Switchover time in the event of a power failure: 2 - 6 ms
- Automatic restart while the voltage is restored
- Software for controlling and monitoring the connected devices / UPS functions
- Capacity: 600 VA / 360 W
- Input voltage: 220 - 240 VAC
- Input voltage tolerance: 162 - 290 VAC
- Output voltage Voltage regulation: +/- 10 %
- Frequency range: 50 to 60 Hz (+/- 10 %)
- Waveform: Simulated sine wave
- Charging time: 6 - 8 hours (0 - 90 % charge)
- Noise level: <40 dB
- USB charging socket type A: 5 V / 2 A max.
- Operating temperature: 0 - 40 °C
- Operating humidity: 0 - 90 % (non-condensing)
- Dimensions (L x W x H): 293 x 202 x 93 cm
- Weight: 4.5 kg

Attributes

- Installation: Desktop
- Installation: Desktop
- Plug: IEC 60320 C14 inlet
- Power: 600VA – 1000VA
- Technology: Line-interactive

Package contents

- UPS
- QIG
- USB cable
- Mains cable (input)

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	21.00	44.10	36.50	30.00	48,289.50
Packaging Unit Inside	1	5.25	0.00	0.00	0.00	0.00
Packaging Unit Single	1	5.25	36.00	14.50	18.00	9,396.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



DIGITUS
ALL-IN-ONE UPS, LED












DN-170110
All-in-One UPS, 600 VA / 360 W, LED
DIGITUS


DN-170110
All-in-One UPS, 600 VA / 360 W, LED
DIGITUS
Router
FAX / Printer
Laptop / PC
Computer
Monitor
Desk desk
Network Switch


DN-170110
All-in-One UPS, 600 VA / 360 W, LED
DIGITUS