DIGITUS® Fans for use in fan units for network and server cabinets

DN-19 FAN

EAN 4016032194422



Fan replacement for fan units 138 m³/h air circulation, 47 dB/m noise level

The DIGITUS® single fan serves as a replacement for existing DIGITUS® fan units in network and server cabinets. Alternatively, the fan can also be wired and commissioned individually. For example, it serves as an add-on to the DIGITUS® outdoor wall-mounted enclosures (e.g., DN-19 12-U-I-OD), where it can be easily snapped into place inside the enclosure in front of the existing filter.

The DIGITUS® 483 mm (19") accessories are designed to meet the high demands of IT infrastructure and are manufactured in accordance with German quality standards.

- Dimensions: 120 x 120 x 38 mm
- Weight: 530 g
- Single-phase
- Power supply: 230 VAC
- Frequency: 50/60 Hz
- Current: 0.14/0.12 A
- Input power: 22/21 W
- Speed: 2700/3100 RPM
- Air circulation: 130–170 m³/h
- Airflow: 75–85 CFM
- Noise level: 42/47 dbA
- Operating temperature: -30°C to +75°C
- Life cycle: 50,000 hours
- Housing material: Die-cast aluminum alloy
- Impeller Material: UL 94-0 plastic
- Motor Protection: Impedance-Protected
- Ball bearing
- Connection cable: lead wires

Attributes

- Color: black, RAL 9005
- Air flow: 130 m3/min
- Filter: no
- For cabinet series: all
- Inch form factor (IEC 60297): 482.6 mm (19")
- Mounting area: Roof
- Quantity of mounted fans: 1

Package contents

- 1 fan

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	60	28.40	59.50	50.00	46.60	138,635.00
Packaging Unit Inside	1	0.47	27.00	16.00	5.00	2,160.00
Packaging Unit Single	1	0.47	27.00	16.00	5.00	2,160.00
Net single without Packaging	0	0.47	5.00	15.00	30.00	2,250.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:





