DIGITUS® CAT 6 Class E Modular coupling, shielded

DN-93613-1

EAN 4016032266846



CAT 6 modular coupler, shielded RJ45 to RJ45, for panel connection

The modular couplers from DIGITUS® are shielded and offer excellent performance and connection quality for your network. Equipped with 2 RJ45 sockets in the 1:1 assignment, they are suitable for patch panel mounting.

- Transmission property: Category 6
- Application areas: Up to 250 MHz, 1GBase-T
- Standards: ISO/IEC 11801 2nd Ed., EN 50173-1, EIA/TIA 568-C, 802.3af, 802.3at PoE+
- General properties:
- Suitable for 483 mm (19") rack mounting
- 2x RJ45 sockets, 8P8C
- 360° shield contacting
- 1:1 Occupied
- Technical features:
- Housing material: Zinc die-cast, nickel-plated
- RJ45 socket material: ABS UL 94V-0
- Contact RJ45 socket: Nickel-plated phosphor bronze, gold-plated contact
- RJ-45 shielding: Nickel-plated bronze
- Printed circuit board: FR4, UL 94V-0
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Tensile load: 7.7 kg between socket and plug
- Operating temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Socket mating cycle: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- In accordance with IEC 60512-5, IEC 60512-6-5
- Terminal: > 200 acc. to ISO/IEC 11801, IEC 60603-7-5
- Core receptacle: 22-26 AWG solid and stranded conductors
- Insulation resistance: > 500 MOhm
- Contact resistance: < 20 milliOhms
- Dielectric strength: 1000 VDC (contact/contact), 1500 VDC (contact/ground)

Attributes

- Category: CAT 6

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	9.34	36.00	30.00	38.00	41,040.00
Packaging Unit Inside	50	467.00	4.00	17.50	29.00	2,030.00
Packaging Unit Single	1	0.01	2.00	6.00	9.00	108.00
Net single without Packaging	0	0.01	3.30	1.90	2.00	12.54

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:

