DIGITUS® KVM Switch, 4 Port, Single Display, 4K, HDMI®

DS-12880

EAN 4016032468639



Desktop HDMI KVM Switch

With the DIGITUS® 4 Port KVM Switch for single displays, you can operate four 4K-compatible PCs using a single USB keyboard and mouse combination. By pressing a button or hot key, you can switch comfortably between the two PCs and are spared the trouble of replugging all cables. Output to one monitor is provided via the HDMI® output on the rear side. You can also switch between the audio signals for the microphone and speaker. In addition, a USB port is included on the front side for use with other peripheral devices like USB sticks or external hard drives on both PCs. The connected peripheral devices are each assigned to the active PC. Status LEDs on the front side of the switch show you the current configuration at all times. The switch features the added benefits of sturdy metal housing.

Operate 4 PCs using an USB keyboard and mouse combination – switch between two computers by pressing a button

- UHD resolution: 4K / 30 Hz (3840 x 2160p) / subsampling: YUV 4:4:4
- Inputs: 4 x HDMI® inputs (4x1), 4 x USB B, 4 x audio combo socket 3.5 mm jack (microphone, loudspeaker)
- Outputs (console): 1 x HDMI®, 2 x USB A (mouse, keyboard), 2 x stereo audio 3.5 mm jack (microphone, speakers)
- Additional connection on the front: 1 x USB A for additional peripheral devices such as printers or USB sticks
- HDMI® version: 1.4b
- USB specification: USB 2.0 compliant (FullSpeed)
- Supported audio formats: Dolby True HD, DTS HD Master Audio
- Switching between the PCs: Switch on the front panel or hot keys
- Status LED on front panel shows current configuration
- The device is platform-independent and suitable for all operating systems.
- Operating temperature: 0°C ~ 50°C
- Storage temperature: -20°C ~ 60°C
- Operating humidity: 0 - 80% RH (non-condensing)
- Housing material: metal
- Power supply: via USB or optional 9 V DC power supply unit
- Dimensions: 20.2 x 11 x 4.4 cm (WxDxH)
- Weight: 780 g
- Color: Black
- Power supply: AC 100-240V
- Power consumption: 2.7W
- DC-STE connector size: 5.5*2.1mm

Attributes

- Interface: HDMI
- Number of ports: 4

Package contents

- 1 x KVM Switch, 4 Port, Single Display, 4K, HDMI®
- 4 x KVM cable (HDMI®, USB, Audio)
- 1 x QIG

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	8	13.16	29.00	40.00	44.00	51,040.00
Packaging Unit Inside	1	1,645.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1,645.00	21.00	21.00	12.00	5,292.00
Net single without Packaging	0	0.78	11.00	20.20	4.40	977.68

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.


More images:











DS-12880 // KVM Switch, 4-Port, Single Display, 4K, HDMI
Anschlüsse
Connections


DS-12880 // KVM Switch, 4-Port, Single Display, 4K, HDMI
Anschlüsse & LEDs
Connections & LEDs





